
# LED RING LIGHT LR150



### **Forward**

Thank you for purchasing this Godox Product!

This LED Ring Light LR150 is suitable for almost all shooting occasions, which can offer lighting for live, make up, portrait shooting, video, wedding, catchlight,

### Features:

- Bicolor adjustment: steplessly adjust color temperature from 3000K-6000K
- Freely adjust brightness from 1% to 100%
- Included an adapter and a smartphone holder

# **▲** Warning

Always keep this product dry. Do not use in rain or in damp conditions. A Do not disassemble. Should repairs become necessary, this product must be sent to an authorized maintenance center.


A Keep out of reach of children.


As this product do not have waterproof function, please take measures of waterproof in rainy or damp environment.

**A** Do not use the light in the presence of flammable gases, chemicals and other similar materials. In certain circumstance, these materials may be sensitive to the strong light emitting from this flash unit and fire or electromagnetic interference may result.

# **Body**

- 01. Main Body
- 02. Power Switch/Brightness Adjusting Button
- 03. Color Temperature Adjusting Button
- 04. DC Power Socket
- 05. USB Smartphone Charging Socket
- 06. 1/4" Mounting Socket
- 07. Heat Dissipation Slot
- 08. Bracket Mounting Socket





### Included Items

LED ring light x1












**Power Management** 

## Power Supply


DC power supply: please connect the adapter to DC power supply.




### Operation

### 1. Before Usage

Please connect the light to DC power supply.




3. Light Brightness Adjustmer Turn the brightness adjusting button to adjust brightness from 1% to 100%.




### 2. Power ON/OFF

Turn the power switch to power it on or off.



4. Color Temperature Adjustment Turn the color temperature adjusting button to adjust color temperature from 3000K - 6000K.



### **Technical Data**

LED Ring Light	LR150
DC Power Supply	24V/2A
USB Power Output	5V/2A
Power	Approx. 38W
Color Temperature	3000K-6000K
100% Brightness(LUX)0.5m≈	1400
Light Brightness Range	1%~100%
CRI	> 90
TLCI	> 90
LED Beads Quantity	336
Operation Temperature	-10~40°C
Dimension	455x555x45mm
Weight	Black version: 880g
	Pink version: 870g

### GODOX Photo Equipment Co., Ltd.

I Add: Building 2, Yaochuan Industrial Zone, Tangwei Community, Fuhai Street, Bao'an District, Shenzhen, China Tel: +86-755-29609320(8062) Fax: +86-755-25723423 E-mail: godox@godox.com 705-LR1200-01 Made in China FC ( RoHS 🗵 godox.com



